


AMC OCEANFLEX

Application

Low voltage copper cable with a tinned galvanised coating to increase corrosion resistance, suitable for harsher environments such as marine applications. High temperature, flame retardant and chemical resistant sheathing. Reduced insulation wall thickness gives considerable saving in weight and on volume especially in large harness construction. Good resistance to petrol, diesel, lubricating oils & diluted acids, as well as surface abrasion and cut through.

Environmental statement

AMC take every action possible to ensure we are a sustainable, and environmentally aware manufacturer. End of life care; ensure that all cable product is disposed of inline with relevant WEEE Regulations.

Specification

Voltage	12v/24v – 60v Max DC
Cores	Class 5 Conductor (Tinned)
Sheath	PVC
Operating Temperature	-30° to 70°C
Min Bend Radius	<6x OD

Standards (Compliance / Certification)

BS EN 60228:2005

ISO6722-1:2011

ISO19642-7

IEC60332.1.2

Part No.	Conductor Specification (mm)	Conductor Cross Section (mm ²)	Maximum Overall Diameter (mm)	Nominal Current Rating (Amps)	Sheath Colour	Core Colours	Reel Sizes (Metres)
CM02/03	2 x 32/0.20	2 x 1	4.9	16.5	Black	Black, Red	30, 100
CM02/25	2 x 21/0.30	2 x 1.5	6.4	21.0	Black		30, 100
CM02/26	2 x 35/0.30	2 x 2.5	6.7	29.0	Black		30, 100
CM02/11	2 x 84/0.30	2 x 6	9.2	50	Black		30, 100

Typical Applications



CARAVANS AND
MOTORHOMES



NAVIGATION AND
COMMUNICATION
EQUIPMENT



ENGINE ROOMS
AND ENCLOSED
AREAS



AUXILLARY
EQUIPMENT



MOTOR BOATS
(MARINE)



BILGE PUMPS



NAVIGATION LIGHTS
(MARINE)



AUDIO &
ENTERTAINMENT
SYSTEMS



STEERING
(MARINE)

The conductor specifications shown are representative configurations; actual cable strand may differ slightly, but will meet the resistance values shown. Nominal current amperage ratings are provided as a guide only, and can vary depending on the application, condition and environmental factors. If in doubt, please consult a qualified electrician.