


LED Navigation Lights S64 (Standard) for vessels up to 50 m



K2W lights are manufactured to the highest standards in Germany. The LED-Navigation light Series S64 is the premium choice for leisure and commercial maritime. Small and with extremely low energy consumption, the product is used for professional vessels, leisure boats & yachts. The high performance LEDs give all our navigation lights a range of over two or three nautical miles, whilst the masthead light can reach up to six nautical miles.

MZ Code	Product		K2W Code	Weight (g)	Energy Consumption (W)	Visibility (nm)	Diameter / Height (mm)	Voltage (V DC)	Standard Trade
63002	Port Light 2nm - Standard		100.01	330	0.8	2	64 / 54	12 / 24	£ 214.14
63004	Starboard Light 2 nm - Standard		101.02	330	0.7	2	64 / 54	12 / 24	£ 214.14
63006	White Stern Light 2nm - Standard		102	330	0.7	2	64 / 54	12 / 24	£ 214.14
63016	All-Round White 2nm - Standard		105	300	1	2	64 / 54	12 / 24	£ 221.01
63018	Red Green Bicolour Forward Light 2nm - Standard		106.08	330	1.2	2	64 / 54	12 / 24	£ 214.14
63020	Red Green White Tricolour Light 2nm - Standard		107.08	330	1.6	2	64 / 54	12 / 24	£ 225.59
63022	Anchor White /Tricolour Red, Green, White 2nm - Standard		108.08	330	1.6/1.2	2	64 / 54	12 / 24	£ 248.49
63008	Suez, Red Stern Light 2nm - Standard		102.01	330	2.1	3	64 / 54	12 / 24	£ 214.14
63010	Towing Yellow Stern Light 2nm - Standard		102.03	330	0.7	2	64 / 54	12 / 24	£ 214.14
63012	Masthead Steaming White Light 3nm - Standard		103	310	1.8	3	64 / 54	12 / 24	£ 214.14
63014	Masthead Steaming White Light 5nm - Standard		104	310	5	5	64 / 54	24	£ 214.14
63026	Signal All-Round Red Light 2nm - Standard		105.01	300	1.1	2	64 / 54	12 / 24	£ 221.01
63030	Signal All-Round Green Light 2nm - Standard		105.02	300	1	2	64 / 54	12 / 24	£ 221.01
63034	Signal All-Round Yellow Light 2nm - Standard		105.03	300	1	2	64 / 54	12 / 24	£ 221.01
63038	Signal All-Round Blue 2nm - Standard		105.04	300	1	2	64 / 54	12 / 24	£ 221.01
63024	Signal 180° White Light 2nm - Standard		105.00-180	370	0.9	2	64 / 54	12 / 24	£ 221.01
63028	Signal 180° Red Light 2nm - Standard		105.01-180	370	1	2	64 / 54	12 / 24	£ 221.01
63032	Signal 180° Green Light 2nm - Standard		105.02-180	370	0.9	2	64 / 54	12 / 24	£ 221.01
63036	Signal 180° Yellow Light 2nm - Standard		105.03-180	370	0.9	2	64 / 54	12 / 24	£ 221.01



MED-certified

Light source	High Power LED
Operating temperature	-50 °C to 55 °C
Storage temperature	-50 °C to 80 °C
Lifetime	> 120.000 h
Maintenance	Maintenance free
Connection	Two-wire 1 mm ² , about 1,5 m
Housing	Anodized aluminium
	Borosilicate glass
	Stainless steel A316
Protection class	IP 67 / 68
Approvals	0098

Our navigation lights S64 have been tested, approved and certified by DNV Germanischer Lloyd (DNV GL) according to the EU regulations. It corresponds in range, beam angle and colors to the international requirements of the COLREG 1972.